



**DECLARATION OF PERFORMANCE
in accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)**

for the product **ARDEX SN**
No **73086**

1. Unique identification code of the product type: **F-INT CC 25HM**
XS 1
PW-INT CC 25HM
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for joints for facades, sanitary areas and pedestrian walkways

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

ARDEX GmbH
Friedrich-Ebert-Str. 45
58453 Witten
Germany

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

not relevant

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 3 for reaction to fire

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body **MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** with the identification number **0432** performed the test according to EN 15651:2012-12, Part 1, 3 and 4.

The notified body **MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** with the identification number **0432** performed the reaction to fire.

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment was issued:

Not relevant

7. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire:	Class E	EN 15651-1: 2012-12 EN 15651-3: 2012-12 EN 15651-4: 2012-12
Release of chemicals dangerous to health and the environment:	evaluated	
Resistance to flow:	≤ 3 mm	
Loss of volume:	≤ 10 %	
Tensile properties at maintained extension:	passed (NF)	
Tear resistance:	passed (NF)	
Tensile properties: 1) Secant modulus at +23°C: at -30°C:	≥ 0.4 MPa ≤ 0.9 MPa	
Tensile properties at maintained extension in cold climate at - 30°C:	passed (NF)	
Adhesion/cohesion at maintained extension after water immersion at 23°C:	passed (NF)	
Microbiological growth:	0	
Durability:	passed	

When specific technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfills:

Not applicable

8. The performance of the product set out in numbers 1 corresponds to the declared performance set out in number 7. The manufacturer as defined in number 3 is solely responsible for drawing up this declaration of performance

Signed for and on behalf of the manufacturer by:

ARDEX GmbH
Friedrich-Ebert-Str. 45
58453 Witten

Jörg W. Sieksmeier *Erhard Symalla*

Dr. Jörg W. Sieksmeier
R & D Director

Dr. Erhard Symalla
R & D Section Head

Witten, 25th September 2014

(Place and date of issue)